CS100 Lecture 10

C Summary

Contents

- C summary
  - Types
  - Variables
  - Expressions
  - Control flow
  - Functions
  - Standard library
  - Example: `Vector`


C Summary

Types

Types are fundamental to any program: They tell us what our data mean and what operations we can perform on those data.

C is a **statically-typed** language: The type of every expression (except those involving VLAs) is known at **compile-time**.

Arithmetic types



Arithmetic types

- `1 == sizeof(char) <= sizeof(short) <= sizeof(int) <= sizeof(long) <= sizeof(long long)`
- `sizeof(signed T) == sizeof(unsigned T)` for every `T` $\in \{$ `char`, `short`, `int`, `long`, `long long` $\}$
- `short` and `int` are at least 16 bits. `long` is at least 32 bits. `long long` is at least 64 bits.
- Range of signed types: $\left[-2^{N-1}, 2^{N-1}-1\right]$. Range of unsigned types: $\left[0, 2^{N}-1\right]$.
- Whether `char` is signed or not is **implementation-defined**.
- Signed integer overflow is **undefined behavior**.
- Unsigned arithmetic **never overflows**: It is performed modulo 2^N, where N is the number of bits of that type.

Pointer types

`PointeeType *`

- For `T` $\neq$ `U`, `T *` and `U *` are **different types**.
- The value of a pointer of type `T *` is **the address of** an object of type `T`.
- **Null pointer**: The pointer holding the **null pointer value**, which is a special value indicating that the pointer is "pointing nowhere".
  - A null pointer can be obtained from `NULL`.
- `&var` returns the address of `var`. The return type is pointer to the type of `var`.
- Only when a pointer is actually pointing to an object is it **dereferenceable**.
- `*ptr`, where `ptr` is not dereferenceable, is **undefined behavior**.

Array types

`ElemType [N]`

- `T [N]`, `U [N]` and `T [M]` are **different types** for `T` $\neq$ `U` and `N` $\neq$ `M`.
- `N` should be compile-time constant. Otherwise it is a VLA.
- Valid index range: $[0, N)$. Subscript out of range is **undefined behavior**.
- Decay: `a` $\rightarrow$ `&a[0]`, `T [N]` $\rightarrow$ `T *`.

Pointer to array: `T (*)[N]`. Array of pointers: `T *[N]`.

`struct` types

A special data type consisting of a sequence of **members**.

- The type name is `struct StructName`.
- $\texttt{sizeof(struct X)} \geqslant \sum_{\texttt{member} \in \texttt{X}} \texttt{sizeof(member)}$

Variables

Declare a variable: `Type varName`

- `ElemType varName[N]` for array type `ElemType[N]`.
- `T (*varName)[N]` for pointer to array type `T (*)[N]`.

Initialize a variable: `= initializer`

- Brace-enclosed list initializer for arrays and `struct`s: `= { ... }`.
- Designators for arrays: `= {[3] = 5, [7] = 4}`
- Designators for `struct`s: `= {.mem1 = x, .mem2 = y}`.

Initialization

If a variable is declared without explicit initializer:

- For global or local `static` variables, they are **empty-initialized**:
  - `0` for integer types,
  - `+0.0` for floating-point types,
  - null pointer value for pointer types.
- For local non-`static` variables, they are **uninitialized**, holding indeterminate values.

These rules apply recursively to the elements of arrays and the members of `struct`s.

Any use of the value of an uninitialized variable is **undefined behavior**.

Scopes and name lookup

```c
int add(int x, int y) {
  return x + y;
}
int square(int x) {
  return x * x;
}
int main(void) {
  int x; scanf("%d", &x);
  printf("%d\n", square(x));
  if (x == 42) {
    int x = 35;
    printf("%d\n", square(square(x)));
  }
  for (int x = 1; x <= 10; ++x)
    printf("%d\n", square(x + 1));
  return 0;
}
```

Expressions

Expressions = operators + operands.

- Operator precedence, associativity, and evaluation order of operands
  - `f() + g() * h()`, `f() - g() + h()`
- The only four operators whose operands have deterministic evaluation order:
  - `&&` and `||`: short-circuit evaluation
  - `?:`
  - `,` (not in a function call or in an initializer list)

Expressions

- If the evaluation order of `A` and `B` is unspecified, and if
  - both `A` and `B` contain a write to an object, or
  - one of them contains a write to an object, and the other one contains a read to that object

  then **the behavior is undefined**.

Arithmetic operators

`+`, `-`, `*`, `/`, `%`


- Division: truncated towards zero.
- Remainder: `(a / b) * b + (a % b) == a` always holds.
- For `+`, `-`, `*` and `/`, the operands undergo a series of type conversions to a common type.

Bitwise operators: `~`, `&`, `|`, `^`, `<<`, `>>`

Compound assignment operators: `a op= b` is equivalent to `a = a op b`.

Be careful with signed overflows.

Pointer arithmetic



- Pointer arithmetic: `p++`, `++p`, `p--`, `--p`, `p + i`, `i + p`, `p - i`, `p += i`, `p -= i`, `p1 - p2`.
- Pointer arithmetic uses the units of the pointed-to type.
  - `p + i == (char *)p + i * sizeof(*p)`
- Pointer arithmetic must be performed within an array (including its past-the-end position), otherwise **the behavior is undefined**.

Operators

`++`, `--`

- `++a` and `--a` returns the value of `a` after incrementation/decrementation.
- `a++` and `a--` returns the original value of `a`.

`<`, `<=`, `>`, `>=`, `==`, `!=`

- The operands undergo a series of type conversions to a common type before comparison.

Operators

Member access: `obj.member`.

Member access through pointer: `ptr->member`, which is equivalent to `(*ptr).member`.

- `.` has higher precedence than `*`, so the parentheses around `*ptr` are necessary.

Control flow

- `if (cond) stmt`
- `if (cond) stmt1 else stmt2`
- `for (init_expr; cond; inc_expr) stmt`
- `while (cond) stmt`
- `do stmt while (cond);`
- `switch (integral_expr) { ... }`
- `break` and `continue`

Functions

Function declaration: `RetType funcName(Parameters);`

- Parameter names are not necessary, but types are required.
- A function can be declared multiple times.

Function definition: `RetType funcName(Parameters) { functionBody }`

- A function can be defined only once.

Functions

- Argument passing:
  - Use the argument to initialize the parameter.
  - The semantic is **copy**.
  - **Decay** always happens: One can never declare an array parameter.

The `main` function

Entry point of the program (after initialization of all global and local `static` variables).

One of the following signatures:

- `int main(void) { ... }`
- `int main(int argc, char **argv) { ... }`, for passing command-line arguments.
- `/* another implementation-defined signature */`

Return value: `0` to indicate that the program exits successfully.

Standard library

- IO library `<stdio.h>`: `scanf`, `printf`, `fgets`, `puts`, `putchar`, `getchar`, ...
- String library `<string.h>`: `strlen`, `strcpy`, `strcmp`, `strchr`, ...
- Character classification `<ctype.h>`: `isdigit`, `isalpha`, `tolower`, ...
- `<stdlib.h>`: Several general-purpose functions: `malloc` / `free`, `rand`, ...
- `<limits.h>`: Defines macros like `INT_MAX` that describe the limits of built-in types.
- `<math.h>`: Mathematical functions like `sqrt`, `sin`, `acos`, `exp`, ...

Example: `Vector`

A "vector" in linear algebra:

$$\mathbf{x} = \begin{bmatrix} x_1 \\ \vdots \\ x_n \end{bmatrix}.$$

It consists of two things: A sequence of n numbers, and its dimension n.

Example: `Vector`

```
struct Vector {
  double *entries;
  size_t dimension;
};
```

Do not name them with `x` and `n`!

[Best practice] Use meaningful names in programs.

Creation and destruction

```
struct Vector create_vector(size_t n) {
  return (struct Vector){.entries = calloc(n, sizeof(double)),
                         .dimension = n};
}
void destroy_vector(struct Vector *vec) {
  free(vec->entries);
  // Do we need to free(vec)?
}
```

Usage:

```
struct Vector v = create_vector(10);
// some operations ...
destroy_vector(&v);
```

"Deep copy" of `Vector`

The default copy semantics of `Vector` is not satisfactory:

```
struct Vector v = something();
struct Vector u = v;
```

Now `u.entries` and `v.entries` point to the same memory block!

```
destroy_vector(&u);
destroy_vector(&v); // undefined behavior: double free!
```

"Deep copy" of `Vector`

```
void vector_assign(struct Vector *to, const struct Vector *from) {
  to->entries = malloc(from->dimension * sizeof(double));
  memcpy(to->entries, from->entries, from->dimension * sizeof(double));
  to->dimension = from->dimension;
}
```

Is this correct?

"Deep copy" of `Vector`

`free` the memory block that is not used anymore!

```
void vector_assign(struct Vector *to, const struct Vector *from) {
  free(to->entries); // Don't forget this!!
  to->entries = malloc(from->dimension * sizeof(double));
  memcpy(to->entries, from->entries, from->dimension * sizeof(double));
  to->dimension = from->dimension;
}
```

Is this correct?

"Deep copy" of `Vector`

```
void vector_assign(struct Vector *to, const struct Vector *from) {
  free(to->entries); // Don't forget this!!
  to->entries = malloc(from->dimension * sizeof(double));
  memcpy(to->entries, from->entries, from->dimension * sizeof(double));
  to->dimension = from->dimension;
}
```

What happens if `to == from`?

- This is not impossible. Consider `vector_assign(&vecs[i], &vecs[j])` where `i` and `j` have a chance to be equal.

"Deep copy" of `Vector`

```
void vector_assign(struct Vector *to, const struct Vector *from) {
  free(to->entries); // Don't forget this!!
  to->entries = malloc(from->dimension * sizeof(double));
  memcpy(to->entries, from->entries, from->dimension * sizeof(double));
  to->dimension = from->dimension;
}
```

What happens if `to == from`?

- This is not impossible. Consider `vector_assign(&x[i], &x[j])` where `i` and `j` have a chance to be equal.
- The memory block is `free`d, and the data are gone.

"Deep copy" of `Vector`

```
void vector_assign(struct Vector *to, const struct Vector *from) {
  if (to == from)
    return;
  free(to->entries); // Don't forget this!!
  to->entries = malloc(from->dimension * sizeof(double));
  memcpy(to->entries, from->entries, from->dimension * sizeof(double));
  to->dimension = from->dimension;
}
```

Why do we declare the parameters as pointers?

"Deep copy" of `Vector`

```
void vector_assign(struct Vector *to, const struct Vector *from) {
  if (to == from)
    return;
  free(to->entries); // Don't forget this!!
  to->entries = malloc(from->dimension * sizeof(double));
  memcpy(to->entries, from->entries, from->dimension * sizeof(double));
  to->dimension = from->dimension;
}
```

Why do we declare the parameters as pointers?

- For `to`, we need to modify it.
- For `from`, this is a read-only operation. Pass the address to avoid copies.

Equality comparison

```
bool vector_equal(const struct Vector *lhs, const struct Vector *rhs) {
  if (lhs->dimension != rhs->dimension)
    return false;
  for (size_t i = 0; i != lhs->dimension; ++i)
    if (lhs->entries[i] != rhs->entries[i])
      return false;
  return true;
}
```

Here we use `!=` to compare two `double`s directly. It's better to use $|a - b| > \epsilon$, considering the floating-point errors.

`lhs` and `rhs` are pointers, to avoid unnecessary copies.

Basic operations on `Vector`

```
struct Vector vector_add(const struct Vector *lhs, const struct Vector *rhs) {
  assert(lhs->dimension == rhs->dimension);
  struct Vector result = create_vector(lhs->dimension);
  for (size_t i = 0; i != lhs->dimension; ++i)
    result.entries[i] = lhs->entries[i] + rhs->entries[i];
  return result;
}

struct Vector vector_scale(const struct Vector *lhs, double scale) {
  struct Vector result = create_vector(lhs->dimension);
  for (size_t i = 0; i != lhs->dimension; ++i)
    result.entries[i] = lhs->entries[i] * scale;
  return result;
}
```

For `vector_add`, our design is to claim that "the behavior is undefined if the vectors have different dimensions".

Dot product, norm and distance (ℓ_2)

```c
double vector_dot_product(const struct Vector *lhs, const struct Vector *rhs) {
  assert(lhs->dimension == rhs->dimension);
  double result = 0;
  for (size_t i = 0; i != lhs->dimension; ++i)
    result += lhs->entries[i] * rhs->entries[i];
  return result;
}
double vector_norm(const struct Vector *vec) {
  return sqrt(vector_dot_product(vec, vec));
}
double vector_distance(const struct Vector *lhs, const struct Vector *rhs) {
  struct Vector diff = vector_minus(lhs, rhs); // Define this on your own.
  return vector_norm(&diff);
}
```

For `vector_dot_product`, our design is to claim that "the behavior is undefined if the vectors have different dimensions".

Print a `Vector`

```
void print_vector(const struct Vector *vec) {
  putchar('(');
  if (vec->dimension > 0) {
    printf("%lf", vec->entries[0]);
    for (size_t i = 1; i != vec->dimension; ++i)
      printf(", %lf", vec->entries[i]);
  }
  putchar(')');
}
```

Exercise

What if we want to increase the dimension of a `Vector`? Implement the related functionality that reallocates a larger block of memory when needed.

```
void vector_push_back(struct Vector *vec, double x) {
  if (/* reallocation is needed */)
    vector_grow(vec); // Implement this function
  vec->entries[vec->dimension++] = x;
}
```

You may need to add members to `struct Vector`.

What we have done

```
struct Vector {
  double *entries;
  size_t dimension;
};
struct Vector create_vector(size_t n);
void destroy_vector(struct Vector *vec);
void vector_assign(struct Vector *to, const struct Vector *from);
bool vector_equal(const struct Vector *lhs, const struct Vector *rhs);
struct Vector vector_add(const struct Vector *lhs, const struct Vector *rhs);
struct Vector vector_minus(const struct Vector *lhs, const struct Vector *rhs);
struct Vector vector_scale(const struct Vector *lhs, double scale);
double vector_dot_product(const struct Vector *lhs, const struct Vector *rhs);
double vector_norm(const struct Vector *vec);
double vector_distance(const struct Vector *lhs, const struct Vector *rhs);
void print_vector(const struct Vector *vec);
```

Problems of the current implementation

1. The call to `create_vector` is not mandatory. One can easily create a `Vector` with some garbage values.
2. `destroy_vector` is not called automatically. If we forget to call it manually, memory leak happens.
3. We always need to pass the address of `Vector`s to these functions. The extra `&` and `*` are annoying.
4. The "deep copy" is implemented by a function, but the default copy semantics are still there. If we forget to call `vector_assign` when copying a `Vector`, disaster will happen.
5. No prevention from modifying a `Vector`: Disaster is caused easily by a simple `free(vec->entries);`.

Problems of the current implementation

6. The named functions are inconvenient: To compute $\mathbf{u}^T(\mathbf{v}+2\mathbf{w})$, we need to write

```
struct Vector scaled = vector_scale(&w, 2);
struct Vector added = vector_add(&v, &scaled);
return vector_dot_product(&u, &added);
```

   Can we express it directly by `return u * (v + 2 * w);`?

7. ……

We will see the solutions to these problems in C++, by data abstraction, and by OOP (object-oriented programming).

Enter the world of C++ ...

From *The Design and Evolution of C++*, by Bjarne Stroustrup who invented C++:

> C++ is a general-purpose programming language that
>
> - is a better C, and
> - supports data abstraction, and
> - supports object-oriented programming.

```
#include <iostream>

int main() {
  std::cout << "Hello world\n";
  return 0;
}
```

Exercise 1: Trace the program

```c
int update(int a[], size_t n) {
  static int calls = 0;
  int sum = 0;
  for (size_t i = 0; i < n; ++i)
    sum += a[i]++;
  return sum + ++calls;
}
int main(void) {
  int a[5] = {[1] = 2, [3] = 4};
  int s = update(a, 5);
  {
    int s = 2;
    printf("%d ", s);
  }
  printf("%d %d\n", s, update(a, 5));
  return 0;
}
```

Assume the required headers are included. Use C17 rules.

1. What is printed? What are the final elements of `a`?
2. Why does `update` modify the caller's array? Does the inner `s` change the outer `s`?

Exercise 2: Copy an integer array

```c
int *copy_array(const int *src, size_t n) {
  int *copy = malloc(n);
  for (size_t i = 0; i <= n; ++i)
    copy[i] = src[i];
  return copy;
}
int main(void) {
  int src[3] = {2, 4, 6};
  int *copy = copy_array(src, 3);
  if (copy == NULL)
    return 1;
  copy[0] = 9;
  printf("%d %d\n", src[0], copy[0]);
  free(copy);
  return 0;
}
```

Assume the required headers are included. The input has n > 0 elements.

1. Repair `copy_array`: check the allocation size, loop bound, and allocation failure.
2. After the repair, what is printed? Why does changing `copy[0]` leave `src[0]` unchanged?
3. Can `main` call `free(src)`? Explain.